

Compact

Versatile solutions for small spaces



Unique Features



Large Capacity — easy loading less often for increased production



Top Quality Stepping Motor — ensures superb performance



DIP Switches — easy setting of common functions



Adjustable Reflective Sensor with Optional Adapter — high flexibility

Postek

Durability to Trust

C168 Series Compact Barcode Label Printer

Long lasting durability and ease of use, plus affordability are the hallmarks of the C168 Series direct thermal/thermal transfer compact printers.

These small power performers feature an astonishing large ribbon capacity of 360 M that limits downtime for reloading. Furthermore, as standard, these printers include an external media stand accommodating larger media rolls and optimizing production uptime. All models are equipped for fast printing speeds and carry a powerful 32-bit processor enhancing efficient label throughput.

3 function buttons and 3 LED lamps make operations easy. Plus, DIP switches offer set-it-and-forget-it convenience. The two printing modes and an adjustable Reflective Media Sensor affords users a wider range of media choices and printing flexibility; the optional media adapter further extends media choices to accommodate extra thin widths to a minimum of 8 mm.

Under the hood is a solid frame and a highly reliable motor and transmission system. These structural components produce the benefits of enhanced stability, top quality output, minimum downtime and low service costs.

For reliable performance with durability to trust, count on the dynamic:

Postek C168 Series.

Industry Solutions

- | | |
|------------------------------|------------------------------|
| Asset Management | Order Labeling |
| Compliance Labeling | Prescription Labeling |
| Fleet Vehicle Identification | Product Labeling and Tagging |
| Healthcare | Shipping / Receiving |
| Information Labels | Retail Point of Sale |
| Inventory Control | Transportation & Logistics |
| Lab Specimen Labeling | Work-in-Process Tracking |
| Medical Record Labeling | |



Specifications

| | | |
|----------------------------|---|------------------------|
| Model | C168/200s | C168/300s |
| Printing Method | Direct Thermal and Thermal Transfer | |
| Resolution | 203 dpi (8 dots/mm) | 300 dpi (11.8 dots/mm) |
| Printing speed | 4 ips (101.6 mm/s) | 3 ips (76.2 mm/s) |
| Max printing width | 4.25" (108 mm) | 4.17" (106 mm) |
| Max printing length | 157" (4000 mm) | 79" (2000 mm) |
| CPU / Memory | 32-bit ARM Processor / 2 MB FLASH ROM, 8 MB SDRAM | |
| Media | Width: 4.3" (110 mm) max., 0.98" (25 mm) min., or with adapter .31" (8 mm) min. Supply roll: OD 4" (102 mm) max., ID 1" (25.4 mm) min. Thickness: 0.003" ~ 0.007" (0.08 ~ 0.18 mm), including liner | |
| Ribbon | Ribbon roll: OD 3" (76.2 mm) max., ID 1" (25.4 mm) core Max width: 4.3" (110 mm); Max length: 1181.10' (360 m). Ink side: Out | |
| Media Sensors | Reflective (Adjustable) | |
| Fonts | Five built-in ASCII fonts | |
| Bar Code Types | ID: Code 39, Code 93, Code 128/subset A,B,C Codabar, Interleave 2 or 5 UPC A/E 2 and 5 add-on, EAN-13/8/128, UCC-128 2D: MaxiCode, PDF 417, Data Matrix, QR | |
| Interfaces | RS-232 Serial, USB | |
| Dimensions | W 9.3" (236 mm) x D 11.4" (291 mm) x H 7.8" (199 mm) | |
| Optional | Rotary Cutter, External Rewinder, Media Guide Adapter and Internal 10/100M Ethernet Card | |
| Warranty | Printers (except normal wear items) and spare parts: 36 months Wear items (printhead, platen roller) and optional accessories: 12 months | |

All specifications are subject to change without notice.

Label Examples



Visit us at www.postektechnologies.com

Postek

Postek Technologies, Inc.
4301 Vineland Rd., Suite E6
Orlando, FL 32811

T | (407) 843.9939
F | (407) 843.9938